

This is implicitly defined for cluster events and does not need to be stipulated explicitly.

7.6.2. Write Access

Write access means that a request to modify attribute data values SHALL be supported. This access modifier SHALL only be defined for cluster attribute data definitions. This access modifier SHALL NOT be defined for cluster event and command definitions.

A cluster specification SHALL define the conditions when write access attribute data is not writable, and SHALL define normative or recommended behavior to follow when this occurs.

An implementation that does not support write access for a field with optional write access SHALL have this declared in its product Declaration of Conformity.

7.6.3. Invoke Access

Invoke access means that a request to execute a command SHALL be supported. This access modifier SHALL only be defined for cluster command definitions, by defining an appropriate privilege level for the command. This access modifier SHALL NOT be defined for cluster event and attribute data definitions.

7.6.4. Fabric-Scoped Access

This access modifier defines that a data model element is scoped to an [associated fabric](#).

When applied to a data element this access modifier defines that element as [fabric-scoped data](#).

This access modifier MAY be applied to the following data model [elements](#):

- Attributes
- Structs
- Commands

7.6.4.1. Attributes

- When this access modifier is applied to an attribute, the attribute SHALL be defined as a [fabric-scoped list](#).

7.6.4.2. Structs

- When this access modifier is applied to a struct, the struct SHALL be a [fabric-scoped struct](#).

7.6.4.3. Commands

- When this access modifier is applied to a command, it requires the command to have an associated fabric to succeed.