

7.6.5. Fabric-Sensitive Access

This access modifier further restricts access to data that is sensitive to the [associated fabric](#).

This access modifier acts as an additional constraint over those imposed by the fabric-scoped access, namely:

- Fabric-sensitive data SHALL NOT be readable unless the [accessing fabric](#) is the [associated fabric](#) of the data. See [Section 7.5.3, “Fabric-Scoped Data”](#).
- A cluster command SHALL NOT return fabric-sensitive data if the [accessing fabric](#) is not the [associated fabric](#) of the data.

Data that is fabric-sensitive SHALL always be fabric-scoped.

This access modifier MAY be applied to the following data model [elements](#):

- Attributes that are lists of [fabric-scoped structs](#)
- Fields of a [fabric-scoped struct](#)
- Events

7.6.5.1. Attributes

- When applied to an attribute, this access modifier defines the attribute as a [fabric-scoped list](#) that is always read as a [fabric-filtered list](#).

7.6.5.2. Struct fields

- When applied to a field of a struct, this access modifier indicates that the field’s value is only available to the struct’s [associated fabric](#).

7.6.5.3. Events

- When applied to an event, the event is defined as a [fabric-sensitive event](#).

7.6.6. View Privilege

An element with the View privilege SHALL support Read (if readable) and Invoke (if invocable) access if the source of the request is granted the View privilege.

A command with the View privilege defined SHALL NOT alter data that is part of its function (e.g. settings, configuration), but MAY alter data that is internal or diagnostic in nature (e.g. usage statistics).

7.6.7. Operate Privilege

An element with the Operate privilege defined SHALL support Read (if readable), Write (if writable), and Invoke (if invocable) access if the source of the request is granted the Operate privilege.