

7.7.9. Scene Quality

This quality is supported and described in the Scenes Management cluster. It relates to the ability of a field to be settable by Scenes. This quality SHALL only apply to attributes having unsigned integer or boolean data types of size at most 4 bytes from the Base Data Types list (e.g. bool, uint8, uint16, uint32), or derived types thereof (e.g. enum8, map8). This quality has no effect in contexts unrelated to the Scenes Management cluster.

7.7.10. Nullable Quality

See [Nullable](#).

7.7.11. Atomic Quality

This quality indicates that an attribute requires atomic writes. See [Atomic Writes](#).

An attribute with this quality SHALL support [Write Access](#).

7.8. Node

A Node is an addressable entity which supports the Matter protocol stack and (once Commissioned) has its own Operational Node ID and Node Operational credentials. It is a unique resource on the network that has a set of functions and capabilities that a user may recognize distinctly as a functional whole.

This distinction is usually physical, such as the physical device itself, or a logical instance of a physical device.

A node is the highest or outermost first order element in the data model. A node is the outermost unique addressable element of the data model.

A node MAY have multiple Operational Node IDs and Node Operational Credentials, with each ID scoped to a particular fabric. When an Operational Node ID is used as the target address of an interaction, the fabric under which the ID is scoped is the [accessing fabric](#) for the interaction.

The lower layers in a communication stack supporting this data model SHALL support interactions between nodes on a logical inter-network of nodes. See [Interaction Model Specification](#) and [System Model Specification](#) that describe relationships and interactions between nodes and data model elements on each node.

It is possible for parts of a node to reside on different processors (e.g. separate application and network processors).

A physical device MAY host multiple nodes.

7.9. Endpoint

A node is composed of one or more endpoints. An endpoint is an instance of something that could be a service or virtual device as indicated by a [device type](#). An endpoint is a particular component