

## 7.10.8. Cluster Classification

A cluster SHALL be defined as either a utility cluster or an application cluster.

### 7.10.8.1. Utility Cluster

A utility cluster is not part of the primary application operation of an endpoint. It may be used for configuration, discovery, addressing, diagnostics, monitoring device health, software update, etc. It may have a temporary relationship with its cluster counterpart.

Utility cluster examples scoped to an endpoint: Identify, Descriptor, Binding, Groups, etc. Utility cluster examples scoped to the node: Basic Information, various Diagnostics clusters, OTA update related clusters, etc.

### 7.10.8.2. Application Cluster

An application cluster supports the primary operation of the endpoint. An application cluster supports one or more persistent application interactions between client and server.

Example application cluster transactions:

- On/Off cluster - client sends command to server
- Temperature Measurement cluster - server reports data to client

An application cluster is not a utility cluster even though it may support utility functions for itself, such as calibration, modes of operation, etc. An application cluster specification SHALL be agnostic about layers and processes outside of its application domain.

Example: A particular temperature measurement cluster may exist on different devices, or in different networks, each with different security & commissioning mechanisms and/or policies.

Example: A commissioning cluster's domain is commissioning, but not temperature measurement.

## 7.11. Command

A cluster command is a set of [data fields](#), each of a [data type](#) that is conveyed between client and server cluster instances to invoke a behavior on the receiver of the command.

Each command SHALL be listed in a table with [data quality](#) columns: ID, Name, Direction, Response, Access, Conformance.

- The command table SHALL define the direction of the command as either client to server or server to client.