

Table 94. Global Fields

| ID   | Name               | Element               | Type       | Con-<br>straint | Quality | Access | Fallback | Confor-<br>mance |
|------|--------------------|-----------------------|------------|-----------------|---------|--------|----------|------------------|
| 0xFE | <b>FabricIndex</b> | struct or event field | fabric-idx | 1 to 254        |         | R V F  |          | fabric-scoped    |

Table 95. Global Commands

| ID   | Name                  | Direction                   | Response       | Access | Conformance   |
|------|-----------------------|-----------------------------|----------------|--------|---------------|
| 0xFE | <b>AtomicRequest</b>  | client $\Rightarrow$ server | AtomicResponse | O      | desc          |
| 0xFD | <b>AtomicResponse</b> | client $\Leftarrow$ server  | N              |        | AtomicRequest |

### 7.13.1. ClusterRevision Attribute

The ClusterRevision attribute indicates the revision of the server cluster specification supported by the cluster instance. An implementation of a cluster specification before the ClusterRevision attribute was added SHALL have an assumed cluster revision of 0 (zero). For a new cluster specification, the initial value for the ClusterRevision attribute SHALL be 1 (not zero).

A history of revision numbers for a cluster specification release is listed in the Revision History section for a cluster specification. Each new revision of a cluster specification SHALL specify a new revision number incremented (by 1) from the last. The highest revision number in a cluster specification's Revision History is the revision number for the cluster specification. Therefore, a ClusterRevision attribute value SHALL be the (highest) revision number of the cluster specification that has been implemented.

### 7.13.2. FeatureMap Attribute

Each instance of a cluster SHALL support this attribute.

The FeatureMap attribute SHALL indicate whether the server supports zero or more optional cluster features. A cluster feature is a set of cluster elements that are mandatory or optional for a defined feature of the cluster. If a cluster feature is supported by the cluster instance, then the corresponding bit SHALL be set to 1, otherwise the bit SHALL be set to 0 (zero). All undefined bits in this attribute SHALL be set to 0 (zero).

The set of cluster elements that are designated as mandatory (M) are implicitly part of the mandatory cluster feature set, and do not have a bit in the FeatureMap attribute.

A cluster specification SHALL support this attribute if the cluster supports features. If a cluster specification is revised to support features (and so this attribute), each bit in the FeatureMap attribute SHALL have a defined default value (1 or 0), to conform with the previous revision of the cluster specification, that did not support the FeatureMap attribute. The value of 1 means the feature elements were mandatory (M) in the previous revision. The value of 0 (zero) means the elements were optional in the previous revision.