

Any newly created feature set of a cluster SHALL be dependent on that cluster.

Feature sets are revision controlled as part of a cluster using the [ClusterRevision attribute](#). The cluster specification is the independent element that is revision controlled. A remote application reading the [FeatureMap](#) and [ClusterRevision attribute](#) will then know exactly what features are supported in the cluster instance.

Each feature set SHALL be well defined within the cluster specification. Each feature SHALL be mapped to a short capitalized code name for the feature set to be referenced as a [conformance tag](#) in the cluster specification text, including the Conformance columns defining the elements of the cluster.

If a cluster defines more than 32 feature sets, then it will be necessary to add another feature bitmap attribute. Any client trying to reference the new feature set will know about the new bitmap, because it knows about the new feature set(s). Legacy products will not know about the new feature set nor the new bitmap.

For a cluster whose definition which does not define a FeatureMap, the server SHALL set this attribute to 0 (zero).

See [Section 7.3.16, “Feature Conformance”](#) for details on conformance.

7.13.3. AttributeList Attribute

Each instance of a cluster SHALL support this attribute. This attribute SHALL be a list of the attribute IDs of the attributes supported by the cluster instance.

7.13.4. AcceptedCommandList Attribute

This attribute is a list of client generated commands which are supported by this cluster server instance.

Each instance of a cluster SHALL support this attribute.

This attribute SHALL be a list of the command IDs for client generated commands that are supported and processed by the server.

For each client request command in this list that mandates a response from the server, the response command SHALL be indicated in the GeneratedCommandList attribute.

If any attribute on a server supports atomic writes, this attribute SHALL contain the command ID for AtomicRequest.

7.13.5. GeneratedCommandList Attribute

This attribute is a list of server generated commands. A server generated command is a server to client command.

Each instance of a cluster SHALL support this attribute.

This attribute SHALL be a list of the command IDs for server generated commands.