

For each command in this list that is a response to a client request command, the request command SHALL be indicated in the `AcceptedCommandList` attribute.

If any attribute on a server supports atomic writes, this attribute SHALL contain the command ID for `AtomicResponse`.

7.13.6. FabricIndex Field

This field SHALL be present for [fabric-scoped data](#). This field does not have to be defined explicitly in the field table for fabric-scoped data.

This field SHALL NOT be present in a write interaction. For a write interaction, the server SHALL provide the value of the [accessing fabric-index](#) as the `FabricIndex` field value to processing logic, after receipt of the interaction. For a [read](#) interaction this field SHALL be included in all reported data that is defined as fabric-scoped.

7.13.7. AtomicRequest Command

This command begins, commits or rolls back atomic writes. See [Section 7.15.6, “AtomicRequest”](#).

This command SHALL be supported by any cluster instance which has attributes with the [Atomic Quality](#).

7.13.8. AtomicResponse Command

This command is returned in response to an `AtomicRequest` command. See [Section 7.15.7, “AtomicResponse”](#).

This command SHALL be supported by any cluster instance which has attributes with the [Atomic Quality](#).

7.14. Event

An event defines a record of something that occurred in the past. In this regard, an event record can be thought of as a log entry, with an event record stream providing a chronological view of the events on the node.

Unlike attributes, which do not provide any edge-preserving capabilities (i.e. no guarantees that every attribute change will be conveyed to observers), events permit capturing every single edge or change and conveying it reliably to an observer. This is critical for safety and security applications that rely upon such guarantees for correct behavior.

Each cluster event is listed in a table that defines: [ID](#), [Priority](#), [Access](#), [Quality](#), [Conformance](#).

Absence of a [Quality](#) column implies that the event does not support any qualities.

Event records are [readable](#), and do not require the read access modifier to be explicitly defined.

Each generated event record SHALL have an event priority that MAY override the defined priority for that event.