

Stage	Action	Action Flow	Description
3	Invoke AtomicRequest	Client $\Rightarrow$ Server	Commits or cancels atomic write
	Return AtomicResponse	Client $\Leftarrow$ Server	Acknowledges commit of atomic write or returns error

Atomic writes have three stages:

1. The client requests to begin an atomic write by providing a list of attributes with the Atomic Write quality and a timeout for completing its expected writes
 - a. The server responds with a list of [attribute statuses](#), and possibly an alternative timeout
 - b. If the client does not accept the statuses or the alternative timeout, then the client SHALL cancel the atomic write using a [Rollback Write](#) request.
2. Otherwise, the client makes a series of write requests to the attributes
 - a. The server pends these writes in an internal buffer, potentially returning errors if a write can not possibly succeed during a commit
3. If the client no longer wants to continue, then it requests to roll back the atomic write; otherwise, the client requests to commit the atomic write
 - a. The server evaluates all the writes, and either applies all of them or returns an error to the client, discarding the pending writes

7.15.2. Atomic Writer ID

An Atomic Writer ID is an [Operational Node ID](#) which identifies the client within the [accessing fabric](#).

If the session context for the transaction is a [Secure Session Context](#), the Atomic Writer ID SHALL be the Peer Node ID stored in the context.

If the session context for the transaction is a [Groupcast Session Context](#), the Atomic Writer ID SHALL be invalid.

An Atomic Writer ID that is not a valid [Operational Node ID](#) SHALL be invalid.

7.15.3. Atomic Write State

An Atomic Write State associates a client with a set of atomic attributes on a server. It is the combination of:

1. An endpoint-no
2. A cluster-id
3. An [Atomic Writer ID](#)
4. The [accessing fabric](#)