

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	StatusCode	status				M
1	AttributeStatus	list[AtomicAttributeStatusStruct]				M
2	Timeout	uint16				desc

7.15.7.1. StatusCode Field

This field SHALL indicate the status of the atomic write. See [Section 7.15.6, “AtomicRequest”](#).

7.15.7.2. AttributeStatus Field

This field SHALL indicate a list of statuses for the attributes involved in the atomic write. This list SHALL contain a status for each of the attribute IDs provided in the AtomicRequest. See [Section 7.15.6, “AtomicRequest”](#).

7.15.7.3. Timeout Field

This field SHALL indicate an effective timeout provided by the server. If the value of the Request-Type field in the AtomicRequest is BeginWrite, this field SHALL be included, otherwise it SHALL be omitted. See [Section 7.15.6, “AtomicRequest”](#).

7.16. Device Type

In this architecture model, a device type is the highest semantic element. A device type defines conformance for a set of one or more endpoints. A device type defines a set of requirements for the node or endpoint in the market.

A device type SHALL define the cluster support for an endpoint. A composed device type MAY define one or more other device types as part of the composed device type.

A device type definition MAY define or use predefined conditions from requirements, limitations and/or capabilities of the node. A device type definition MAY define or use predefined conditions on one or more underlying stack standard(s).

A device type MAY assert conditions defined in itself or in other device types. See [Section 9.2.6, “Asserting Conditions Among Device Types”](#) for details.

A device type MAY define support of a cluster as dependent upon a condition. A device type definition MAY specify optional clusters that are recommended as enhancements.

A device type definition MAY refine cluster conformance:

- Support of optional cluster elements or features MAY be changed to mandatory depending on device type conditions.
- Support of optional cluster elements or features MAY depend on device type conditions.