

- A struct itself SHALL have no constraint qualities.
- Each struct field SHALL have its own qualities.
- Access, conformance and persistence qualities, when not explicitly defined, SHALL be inherited from the instance of the struct itself.
- Struct fields MAY have optional conformance.
- A struct SHALL support reading and reporting of all fields.
- A struct SHALL support reporting changes to one or more fields.
- If the struct is writable, it SHALL support writing the entire struct.
- If a field of the struct is writable, the struct SHALL support updating the field.
- Because of optional struct field conformance, instances of the same struct MAY support multiple 'flavors' of the same struct data type, but with a different set of optional fields.

Fabric-Scoped Struct

- A fabric-scoped struct SHALL only be defined and occur as an entry in a fabric-scoped list.
- A fabric-scoped struct SHALL support the [global FabricIndex field](#) of type [fabric-index](#), which indicates the [associated fabric](#) of the struct, or indicates that there is no associated fabric.
- The table that defines fields of a fabric-scoped struct SHALL NOT list the [global FabricIndex field](#), which is a global field and defined implicitly.
- The [global FabricIndex field](#) of a fabric-scoped struct SHOULD NOT be indicated in a write interaction.
- The [global FabricIndex field](#) of a fabric-scoped struct SHALL be ignored in a write interaction.
- The [global FabricIndex field](#) SHOULD NOT be indicated on a fabric-scoped struct contained in the payload of a request command.
- The [global FabricIndex field](#) SHALL be ignored on a fabric-scoped struct contained in the payload of a request command.
- When a [write](#) interaction creates a fabric-scoped struct entry (in a fabric-scoped list), the server SHALL implicitly load the [accessing fabric-index](#) into the [global FabricIndex field](#) of the struct.
- When the payload of a request command contains a fabric-scoped struct, the server SHALL implicitly load the [accessing fabric-index](#) into the [global FabricIndex field](#) of the struct.
- A fabric-scoped struct MAY be defined with some fields that are [fabric-sensitive](#).
- For interactions on a fabric-scoped struct that report back data, fabric-sensitive struct fields SHALL be omitted when reporting data back to the client, when the struct has an [associated fabric](#), and it is not the [accessing fabric](#).

7.19.2. Derived Data Types

These data types are commonly used and derived from the base data types. If a data type is used by more than one cluster specification, then it SHALL be listed here as a derived data type. Such common data types can then be reused instead of redefined in each cluster specification.