

see uses of the [SemanticTagStruct](#) data type that supports many (and any) standard namespaces.

Undefined values or ranges SHALL be considered reserved and SHALL NOT be implemented.

External standards may be referenced as well as listing the values for the external standard. If the external standard adds values after a specification is adopted, those new values are allowed, but optional.

Enumeration values are defined in a table with a Conformance column. When the definition of an enumeration is missing a Conformance column, all values SHALL be considered to have mandatory conformance.

All mandatory readable enumeration values SHALL be understood by the client. All mandatory writable enumeration values SHALL be understood by the server.

If a client indicates an enumeration value to the server, that is not supported by the server, because it is optional, deprecated, or a new value unrecognized by a legacy server, then the server SHALL respond with the status code `CONSTRAINT_ERROR`, unless the cluster defines alternate behavior, such as:

- convert the value to a mandatory value
- ignore the value
- generate a cluster specific error

With regard to revising a cluster specification:

- It is RECOMMENDED that a client be as strict as possible by indicating only values that a server supports.
- It is RECOMMENDED that the server be as forgiving as possible when processing unsupported values.

Note that indicated enumerations MAY comprise only a strict subset of the required enumerations.

For example: If a server implementation can never enter an enumerated state *XYZ*, then the value *XYZ* would never be indicated, therefore the server would not have to support *XYZ*.

8-bit Enumeration

This type is used for enumeration types that need no more than 256 possible values.

16-bit Enumeration

This type is used for enumeration types that need more than 256 (but less than 65,536) possible values.

7.19.2.20. Priority Type

This is an enumeration of priority used to tag events and possibly other data. The data type does not define any particular ordering among the values. Specific uses of the data type may assign