

7.19.2.51. CurrencyStruct Type

This data type represents a currency with an associated number of decimal points.

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	Currency	uint16	max 999				M
1	Decimal-Points	uint8	all				M

7.19.2.52. Currency Field

This field SHALL indicate the numeric currency code. The value of the currency field SHALL match one of the numeric currency code values defined by [ISO 4217](#).

7.19.2.53. DecimalPoints Field

This field SHALL indicate the number of digits to the right of the decimal point in values of the specified currency.

7.19.2.54. PriceStruct Type

This data type represents an amount of money in a given currency.

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	Amount	money	all				M
1	Currency	Section 7.19.2.51, “CurrencyStruct”					M

7.19.2.55. Amount Field

This field SHALL indicate the amount of money as specified by the [currency code](#) and [number of decimal places](#) in the [Section 7.19.2.56, “Currency”](#) field. See [Section 7.19.2.18, “Money”](#).

7.19.2.56. Currency Field

This field SHALL indicate the currency for the value in the [Section 7.19.2.55, “Amount”](#) field.

7.20. Units

In order to align units across clusters, the following base units are defined to be used when adding elements that use one of the units listed in the table below. These base units are based on the SI-units, with an exception for Temperature where Celsius is more widely used in day-to-day measurements. Clusters created before these base units were defined MAY diverge from the use of these units, for legacy elements only. When adding new elements of one of the types defined below, the