

[fabric](#) for the interaction.

- SuppressResponse MAY be set to TRUE for a Report Data action that initiates a Report transaction that conveys an empty list of AttributeReports and EventReports, otherwise:
 - SuppressResponse SHALL be set to TRUE for a Report Data action that is part of a Read transaction.
 - SuppressResponse SHALL be set to FALSE for a Report Data action that is part of a Subscribe transaction.
- This action SHALL be generated as either:
 - part of a Read transaction in direct response to a Read Request action.
 - part of a Subscribe transaction in direct response to a Subscribe Request action.
 - part of a Subscribe interaction as the first action of each synchronized [Report Transaction](#).

8.4.3.4. Incoming Report Data Action

- Upon receipt of this action, if SuppressResponse is TRUE, a response SHALL NOT be generated;
- Otherwise a [Status Response Action](#) SHALL be generated with a status code of
 - SUCCESS to continue the interaction,
 - INVALID_SUBSCRIPTION if the action is part of a Subscribe interaction and the SubscriptionID is invalid,
 - FAILURE to terminate the interaction,
 - The [Status Response Action](#) SHALL be submitted to the message layer to deliver to the source of this action.

8.5. Subscribe Interaction

The Subscribe interaction is composed of these transactions:

Transaction	Description
Subscribe	start and prime a reporting session
Report	synchronized Report transaction
<i>more reports</i>	continuous Report transactions for the life of the subscription

This interaction allows a subscriber to create a subscription with a publisher on another node for the purposes of receiving data reports from that publisher thereafter, for the duration of the subscription. This allows the subscriber to maintain a coherent snapshot, or twin, of the subscription data as it currently exists on the publisher. The session itself is kept synchronized on both sides through the receipt of timely data reports with the intervals defined by a negotiated maximum interval subscription parameter.

This interaction is started when the initiator (or subscriber), wishes to subscribe to one or more attributes or events located on a target node (the publisher). The attribute data and events