

- If the subscriber does not receive a [Report transaction](#) within the maximum interval from the last Report Data, the subscriber SHALL terminate the Subscribe interaction.
- If a node receives a Report Data action with an inactive SubscriptionId, a Status Response action SHALL be sent with an INVALID_SUBSCRIPTION Status Code.
- If, in response to a Report Data action, the publisher receives a Status Response action with a status code that is not SUCCESS, the publisher SHALL terminate the Subscribe interaction.
- If the publisher does not receive a Status Response action in response to a Report Data action with SuppressResponse set to FALSE, the publisher MAY terminate the Subscribe interaction or SHALL re-synchronize the subscription in the next Report Data transaction by:
 - Including all subscription data to re-prime the subscription, or
 - Including all deltas since the last successful Report Data transaction.
- The subscriber MAY terminate the subscription and interaction by responding with a Status Response action with an INVALID_SUBSCRIPTION Status Code.
- The publisher MAY terminate the subscription and interaction by not generating a [Report transaction](#) within the maximum interval.
- When a Subscribe interaction is terminated on the publisher or subscriber, the subscription, identified by a SubscriptionId, SHALL also be terminated.

8.5.1. Subscribe Transaction

Action	Action Flow	Description
Subscribe Request	Initiator ⇒ Target	list of event and attribute data identifiers supported on a server cluster
Report Data	Initiator ⇐ Target	primed published data
Status Response	Initiator ⇒ Target	success, or otherwise an error to terminate the subscription
Subscribe Response	Initiator ⇐ Target	provides subscription parameters

8.5.2. Subscribe Request Action

Subscribe Request action is a first action. See [Section 8.2.5, “Common Action Behavior”](#) for behavior common to all actions. The specific action information for this action is shown below.

8.5.2.1. Subscribe Request Action Information

Action Field	Type	Conformance	Description
KeepSubscriptions	bool	M	false to terminate existing subscriptions from initiator