

Action Field	Type	Conformance	Description
MinIntervalFloor	uint16	M	the requested minimum interval boundary floor in seconds
MaxIntervalCeiling	uint16	M	the requested maximum interval boundary ceiling in seconds
AttributeRequests	list[AttributePathIB]	O	a list of zero or more request paths to cluster attribute data
DataVersionFilters	list[DataVersionFilterIB]	AttributeRequests	a list of zero or more cluster instance data versions
EventRequests	list[EventPathIB]	O	a list of zero or more request paths to cluster events
EventFilters	list[EventFilterIB]	EventRequests	a list of zero or more minimum event numbers per specific node
FabricFiltered	bool	M	limits the data read within fabric-scoped lists to the accessing fabric

8.5.2.2. Outgoing Subscribe Request Action

- This action SHALL initiate a Subscribe interaction.
- A Subscribe Request action SHALL be unicast from the subscriber to the publisher.
- This action SHALL be generated to initiate a Subscribe interaction (see [Section 8.5, “Subscribe Interaction”](#)).
- This action SHALL include a requested ceiling (highest) maximum interval value as MaxIntervalCeiling.
- This action SHALL include a requested floor (lowest) minimum interval value as MinIntervalFloor.

NOTE

If the publisher is an [intermittently connected device](#), the MinIntervalFloor SHOULD be 0. To avoid needing to switch to Active Mode to process the event and a second time to send the information, an [ICD](#) MAY try to synchronize its updates towards various subscribers so that it only needs to go to Active Mode once and can stay idle for a full idle interval. If the MinIntervalFloor is too high, this limits the freedom for an ICD to synchronize its updates. The higher the MinIntervalFloor is, the higher the likelihood an ICD will not be able to send updates to various subscribers in a synchronized pattern, which might negatively impact energy usage