

8.5.3.3. Incoming Subscribe Response Action

- Upon receipt of a Subscribe Response action, the subscription, as indicated by the SubscriptionId, SHALL become active to the subscriber.

8.5.3.4. Subscription Activation

- The paths to the subscription data SHALL only be error free existent paths generated from processing the Subscribe Request.

The EventFilters and DataVersionFilters fields in the Subscribe Request are one time parameters for the priming of the subscription.

- Subsequent ReportData actions, as part of the subscription, SHALL include the latest:
 - EventNo associated with each node generating new events.
 - DataVersion associated with each cluster where there are data changes.
- The FabricFiltered parameter from the Subscribe Request SHALL remain in effect for all data reported during the interaction.
- Upon subscription activation, the minimum and maximum interval parameters SHALL take effect to determine the timing and expectation of subsequent Report transactions.

8.6. Report Transaction

There is no Report interaction. A Report transaction is part of a Subscribe interaction. See [Section 8.5, “Subscribe Interaction”](#) for details.

The valid Report transactions are:

8.6.1. Report Transaction Non-Empty

Action	Action Flow	Description
Report Data	Initiator $\Leftarrow$ Target	report of data and/or events with SuppressResponse set to FALSE
Status Response	Initiator $\Rightarrow$ Target	an error ends the interaction

8.6.2. Report Transaction Empty

Action	Action Flow	Description
Report Data	Initiator $\Leftarrow$ Target	report with no data or events with SuppressResponse set to TRUE