

- [AttributeStatusIB](#) SHALL be generated with the UNSUPPORTED\_ATTRIBUTE Status Code with the Path field indicating only the path to the first unsupported data field (not the entire attribute data path).
- Else if the path indicates an attribute that is not writable, an [AttributeStatusIB](#) SHALL be generated with the UNSUPPORTED\_WRITE Status Code.
  - Execute the [ACL Access Granting Algorithm](#) against the concrete path a second time, using the actual [required\\_privilege](#) for the attribute referenced in the path.
    - If the outcome is AccessDenied, a [AttributeStatusIB](#) SHALL be generated with the UNSUPPORTED\_ACCESS Status Code.
    - Else if the outcome is AccessRestricted, a [AttributeStatusIB](#) SHALL be generated with the ACCESS\_RESTRICTED Status Code.
    - Otherwise, continue processing.
  - If the path indicates specific attribute data that requires a Timed Write transaction to write and this action is not part of a Timed Write transaction, an [AttributeStatusIB](#) SHALL be generated with the NEEDS\_TIMED\_INTERACTION Status Code.
  - Else if the attribute in the path indicates a fabric-scoped list and there is no [accessing fabric](#), an [AttributeStatusIB](#) SHALL be generated with the UNSUPPORTED\_ACCESS Status Code, with the Path field indicating only the path to the attribute.
  - Else if the DataVersion field of the [AttributeDataIB](#) is present and does not match the data version of the indicated cluster instance, an [AttributeStatusIB](#) SHALL be generated with the DATA\_VERSION\_MISMATCH Status Code.
  - If the above processing generated an [AttributeStatusIB](#), the path SHALL be discarded.
  - Else perform [Write Path Data Process](#)
  - Else perform [Request Path Expansion](#) and process each expanded existent path as follows:
    - If the path indicates attribute data that is not writable, then the path SHALL be discarded.
    - Execute the [ACL Access Granting Algorithm](#) against the path, using the actual [required\\_privilege](#) for the attribute referenced in the path.
      - If the outcome is either AccessDenied or AccessRestricted, then the path SHALL be discarded.
      - Otherwise, continue processing.
    - Else if the path indicates specific attribute data that requires a Timed Write transaction to write and this action is not part of a Timed Write transaction, then the path SHALL be discarded.
    - Else perform [Write Path Data Process](#)

### 8.7.3.3. Write Path Data Process

- If the path indicates a fabric-scoped list or list entry, it SHALL be processed as a [fabric-filtered list](#) of [fabric-scoped structs](#).
- Each data field indicated by the path, SHALL be processed in the order conveyed as follows: