

- If a data field is not within the constraints defined by the cluster specification, an **AttributeStatusIB** SHALL be generated with the CONSTRAINT_ERROR Status Code, with the Path field duplicating the path.
- Otherwise perform the following:
 - The data field SHALL be changed to the data indicated with the path.
 - An **AttributeStatusIB** SHALL be generated with the SUCCESS Status Code, with the Path field duplicating the path.

8.7.3.4. Write Response Generation

- Each **AttributeStatusIB** generated from processing the WriteRequests field of the Write Request action, SHALL be added to the WriteResponses action field of the Write Response action.

NOTE

An empty WriteResponses would occur if all paths were wildcard or group paths that expand to non-accessible data.

8.7.3.5. Incoming Write Response Action

Upon receipt of this action, the action information SHALL be submitted to the layer above.

8.7.4. Timed Request Action

This action is a first action of a transaction. The specific action information for this action is shown below.

This action informs the receiver that another action will be sent in the same direction, within the same transaction, and within a specified Timeout interval. The Timeout interval SHALL start when the Status Response action acknowledging the Timed Request action with a success code is sent.

8.7.4.1. Timed Request Action Information

Action Field	Type	Conformance	Description
Timeout	uint16	M	an interval, in milliseconds, to expect a following action

8.7.4.2. Outgoing Timed Request Action

- This action SHALL be generated as an optional first action in a Write or Invoke transaction.
- This action SHALL be unicast.

8.7.4.3. Incoming Timed Request Action

- Upon receipt of this action, this layer SHALL construct and send a Status Response action with SUCCESS to the initiator.
- This layer SHALL expect a Write Request or Invoke Request action within Timeout milliseconds of sending the Status Response action.