

8.8. Invoke Interaction

This interaction is generated when a device wishes to invoke one or more cluster specific commands on one or more nodes. Cluster commands are defined as either client to server or server to client. Invoke Request action SHALL support [group paths](#) and SHOULD support [wildcard paths](#). Invoke Response action does not support [wildcard paths](#).

8.8.1. Invoke Transaction

- The Invoke interaction SHALL consist of one of the Invoke transactions shown below

8.8.1.1. Timed Invoke Transaction

Action	Action Flow	Description
Timed Request	Initiator ⇒ Target	time interval defined to send Invoke Request action
Status Response	Initiator ⇐ Target	confirmation
Invoke Request	Initiator ⇒ Target	commands to invoke
Invoke Response	Initiator ⇐ Target	response(s) defined by the cluster specification

8.8.1.2. Untimed Invoke Transaction

Action	Action Flow	Description
Invoke Request	Initiator ⇒ Target	commands to invoke
Invoke Response	Initiator ⇐ Target	response(s) defined by the cluster specification

- A client MAY choose to use a Timed Invoke transaction even if the command does not have the Timed Interaction quality.
- The server SHALL support a Timed Invoke transaction for all commands.

8.8.2. Invoke Request Action

- This action SHALL be generated as the first action in an Invoke transaction, or following a Timed Request action and successful Status Response action.
- If there is a preceding successful Timed Request action, the following Invoke Request action SHALL be received before the end of the Timeout interval.
- If there is a preceding successful Timed Request action, the Timeout interval SHALL start when the Status Response action acknowledging the Timed Request action with a success code is sent.
- Each Invoke Request and Invoke Response action in a Timed Invoke transaction SHALL be unicast.
- If not part of a Timed Invoke transaction, this action MAY be groupcast.