

ceding Timed Request action, then a Status Response action with the TIMEOUT Status Code SHALL be submitted to the message layer and this interaction SHALL terminate.

NOTE Devices certified prior to 1.4 MAY return UNSUPPORTED_ACCESS for this condition.

- If this action is part of a Timed Invoke transaction, and this action has TimedRequest set to FALSE, then a Status Response action with the TIMED_REQUEST_MISMATCH Status Code SHALL be submitted to the message layer and this interaction SHALL terminate.
- If this action is marked with TimedRequest as TRUE, but this action is not part of a Timed Invoke transaction (i.e. there was no immediately previous Timed Invoke action), then a Status Response action with the TIMED_REQUEST_MISMATCH Status Code SHALL be submitted to the message layer and this interaction SHALL terminate.
- If this action contains more [CommandDataIB](#) elements in the InvokeRequests list than are supported by the device (see [MaxPathsPerInvoke Attribute](#)), then a Status Response action with the INVALID_ACTION Status Code SHALL be submitted to the message layer and this interaction SHALL terminate.
- Each request path in the InvokeRequests field SHALL be processed as follows:
 - If the path does not conform to [Valid Command Paths](#) then:
 - a Status Response with the INVALID_ACTION Status Code SHALL be generated as defined in [Status Response Action](#), an Invoke Response action SHALL NOT be generated, and this interaction and process SHALL terminate.
 - Else if the path is a concrete path, the path SHALL be processed as follows, terminating further processing of the concrete path immediately if a failure [CommandStatusIB](#) is generated at any point (one that is not a status of SUCCESS). If a failure [CommandStatusIB](#) is generated, its CommandPath field SHALL be a duplicate of the concrete path processed, including the command ID of the original concrete path.
 - Execute the [ACL Access Granting Algorithm](#) against the concrete path, assuming the [required_privilege](#) for the element is Operate, to determine whether the subject would have had at least some access against the concrete path.
 - If the outcome is AccessDenied, a [CommandStatusIB](#) SHALL be generated with the UNSUPPORTED_ACCESS Status Code.
 - Else if the outcome is AccessRestricted, a [CommandStatusIB](#) SHALL be generated with the ACCESS_RESTRICTED Status Code.
 - Otherwise, continue processing.
 - Determine element existence from the concrete path, and apply the following checks:
 - If the path indicates a node that is unsupported, a [CommandStatusIB](#) SHALL be generated with the UNSUPPORTED_NODE Status Code.
 - Else if the path indicates an endpoint that is unsupported, a [CommandStatusIB](#) SHALL be generated with the UNSUPPORTED_ENDPOINT Status Code.
 - Else if the path indicates a cluster that is unsupported, a [CommandStatusIB](#) SHALL be generated with the UNSUPPORTED_CLUSTER Status Code.
 - Else if the path indicates a command that is unsupported, a [CommandStatusIB](#)