

SHALL be generated with the UNSUPPORTED_COMMAND Status Code.

- Execute the [ACL Access Granting Algorithm](#) against the concrete path a second time, using the actual [required_privilege](#) for the command referenced in the path.
 - If the outcome is AccessDenied, a [CommandStatusIB](#) SHALL be generated with the UNSUPPORTED_ACCESS Status Code.
 - Else if the outcome is AccessRestricted, a [CommandStatusIB](#) SHALL be generated with the ACCESS_RESTRICTED Status Code.
 - Otherwise, continue processing.
- If the command in the path has the [Large Message Quality](#) and was received on a transport that is not capable of transporting Large Messages, a [CommandStatusIB](#) SHALL be generated with the INVALID_TRANSPORT_TYPE Status Code.
- Else if the command in the path is fabric-scoped and there is no accessing fabric, a [CommandStatusIB](#) SHALL be generated with the UNSUPPORTED_ACCESS Status Code.
- Else if the command in the path requires a Timed Invoke transaction to invoke and this action is not part of a Timed Invoke transaction, a [CommandStatusIB](#) SHALL be generated with the NEEDS_TIMED_INTERACTION Status Code.
- Else perform [Request Path Expansion](#) and process each expanded existent path as follows:
 - Execute the [ACL Access Granting Algorithm](#) against the path, using the actual [required_privilege](#) for the command referenced in the path.
 - If the outcome is either AccessDenied or AccessRestricted, then the path SHALL be discarded.
 - Otherwise, continue processing.
 - Else if the command in the path requires a [Large Message](#) transport and this action was not received on a transport capable of Large Messages, then the path SHALL be discarded.
 - Else if the command in the path is fabric-scoped and there is no accessing fabric, then the path SHALL be discarded.
 - Else if the command in the path requires a Timed Invoke transaction to invoke and this action is not part of a Timed Invoke transaction, then the path SHALL be discarded.
- Each command in the remaining and error-free concrete command paths SHALL be executed, as defined in [Invoke Execution](#).

Invoke Execution

- The command SHALL be executed as defined in the cluster specification, and the following applies:
 - For each data field in CommandFields:
 - If a mandatory data field is missing, or incoming data cannot be mapped to the expected data type for a field, a [CommandStatusIB](#) SHALL be generated with an error status of INVALID_COMMAND, even if the cluster defines another type of response.
 - If a data field violates expected constraints, a [CommandStatusIB](#) SHOULD be generated