

points would indicate and conform to the temperature sensor device type, and have unique TagList attributes to disambiguate them.

Clusters associated with the component device types MAY have their conformance altered in the Cluster Requirements on Component Device Types table in the composed device type definition.

Elements associated with the component device types MAY have their conformance altered in the Element Requirements on Component Device Types table in the composed device type definition.

Tags associated with the component device types MAY have their conformance altered in the Semantic Tag Requirements on Component Device Types table in the composed device type definition.

For example: Device type A is a composed device type and includes component device type B in its Device Type Requirements table. The definition for device type B includes cluster C in its Cluster Requirements table with optional (O) conformance. Composed device type A lists component device type B and cluster C in its Cluster Requirements on Component Device Types table and alters the conformance for cluster C in device type B to mandatory (M).

9.2.4. Component Device Types

A component device type is a device type that is included in the Device Type Requirements table of a [composed device type](#).

9.2.5. Compound Devices

A compound device is a single physical entity containing multiple device types existing on separate endpoints but for which a composed device type is not defined. A compound device allows a manufacturer to create a product containing multiple device types as seen fit by that manufacturer.

For example: A compound device supporting 2 lighting device endpoints, an "up light" on endpoint 1 and a "down light" on endpoint 2. The root node PartsList contains endpoint 1 and 2. The lighting device types are not defined as composed devices, and no device is defined having such a construction, therefore this device containing multiple lighting device endpoints is a compound device.

For example: A PIR occupancy sensor which also contains a light level sensor and a temperature sensor, would have 3 device endpoints with the corresponding device types (Occupancy Sensor, Light Sensor and Temperature Sensor).

9.2.6. Asserting Conditions Among Device Types

A device type MAY assert conditions defined in itself or other device types which appear on the same or other endpoints of the node, subject to the requirements below.

Definitions: