

specification. A conformance listed as purely optional (O) MAY be used to signal that a condition could be expected to be asserted on the node, which could be helpful to clients.

For details regarding valid conformance designations, see [Section 7.3, “Conformance”](#).

9.2.7. Endpoint Composition Patterns

This specification defines two patterns for endpoint composition supported by a device type:

- Tree pattern of endpoints directly below the composed endpoint.
- Full-family list of all descendant endpoints below the composed endpoint.

The Bridged Node device type has specific requirements on endpoint composition as detailed in the definition of this device type in the Device Library.

9.2.7.1. Tree Pattern

The tree pattern supports a general tree of endpoints, each of which supports the pattern defined by the endpoint's device type. The tree pattern is commonly used for composed application device types. The tree pattern is commonly used for device types that support physical device composition (e.g. a Refrigerator).

- The tree pattern of composition SHALL be defined in the device type specification, by a table of device types, from which the specified device type is composed.
 - Each device type from the table that is included in an implementation SHALL be represented by one or more endpoints in the PartsList attribute of the Descriptor cluster on the endpoint of the parent device type.
 - An implementation MAY include other device types not listed in the table of device types in its composition and each such additional device SHALL be represented by an endpoint in the PartsList attribute of the Descriptor cluster on the endpoint of the parent device type.

For example: A Refrigerator/Freezer endpoint has a PartsList with the Refrigerator and Freezer endpoint, but not the parts of the Refrigerator or Freezer. The Refrigerator and Freezer endpoints each have a PartsList that includes temperature sensor and control endpoints.

9.2.7.2. Full-Family Pattern

The full-family pattern is a list of all descendant endpoints, with no imposed hierarchy.

- The full-family pattern of endpoint composition SHALL be defined in the device type specification by stating that the device type supports the full-family pattern.
- The PartsList attribute of the Descriptor cluster on the endpoint SHALL contain all descendant endpoints.

Example: The Root Node and Aggregator device types use the full-family pattern, as defined