

9.3.1.1. Persistency

A subscription is an ephemeral 'session' between a subscriber and a publisher. A subscription can lose synchronization for a variety of reasons, including (but not limited to):

- Inability to send reports due to network connectivity issues
- Factory-reset of the publisher
- Reboot of either the subscriber or publisher
- Decision by either publisher or subscriber to tear down the subscription to reclaim resources

In all cases, the subscriber can eventually discover the loss of synchronization by not receiving a sync report or data report in the agreed upon sync interval, or through some other failure to communicate with the publisher.

- When a subscriber discovers the loss of synchronization, it MAY then initiate a re-subscription to resume the subscription.
- An implementation MAY choose to persist the details of a subscription across reboots, but it is not necessary.

In all cases, the publisher eventually discovers the loss of synchronization by not receiving a Status Response to a Report Data message that expects a response, or by receiving an error Status Response.

9.4. Binding Relationship

This relationship occurs because a simple client endpoint does not know which endpoints will be the target for the client generated actions, on one or more remote nodes.

For example: A light switch that controls one or more light bulbs, does not know the remote node endpoints of the bulbs.

For example: A thermostat that subscribes to an occupancy sensor, does not know the remote node endpoint of the sensor.

In such cases, a binding is used to direct the local endpoint to the remote endpoint. The existence of the Binding cluster on an endpoint, allows a director to create one or more binding entries (bindings) in the Binding cluster. A director is a remote client that is given access to create such bindings.

Each binding indicates either a remote node's endpoint or cluster on a remote node's endpoint. Multiple bindings are allowed, depending on the interaction. A binding is either a unicast binding, where the binding target is a remote endpoint, or a groupcast binding, where the binding target is a group of remote endpoints.

See the Binding Cluster specification for more specification detail.