

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0x0002	ClientList	list[cluster-id]		F	empty	R V	M
0x0003	PartsList	list[end-point-no]			empty	R V	M
0x0004	TagList	list[Semantic-TagStruct]	1 to 6	F	MS	R V	TAGLIST
0x0005	End-pointUniqueID	string	max 32	F		R V	O

9.5.6.1. DeviceTypeList Attribute

This is a list of device types and corresponding revisions declaring endpoint conformance (see [Section 9.5.5.1, “DeviceTypeStruct Type”](#)). At least one device type entry SHALL be present.

An endpoint SHALL conform to all device types listed in the DeviceTypeList. A cluster instance that is in common for more than one device type in the DeviceTypeList SHALL be supported as a shared cluster instance on the endpoint.

9.5.6.2. ServerList Attribute

This attribute SHALL list each cluster ID for the server clusters present on the endpoint instance.

9.5.6.3. ClientList Attribute

This attribute SHALL list each cluster ID for the client clusters present on the endpoint instance.

9.5.6.4. PartsList Attribute

This attribute indicates composition of the device type instance. Device type instance composition SHALL include the endpoints in this list.

See [Endpoint Composition](#) for more information about which endpoints to include in this list.

9.5.6.5. TagList Attribute

This attribute SHALL be used to disambiguate sibling endpoints in certain situations, as defined in the [Disambiguation section in the System Model specification](#). An example of such a situation might be a device with two buttons, with this attribute being used to indicate which of the two endpoints corresponds to the button on the left side.

It MAY also be used to provide information about an endpoint (e.g. the relative location of a Temperature sensor in a Temperature Controlled Cabinet).

- A client SHOULD use these tags to convey disambiguation information and other relevant infor-