

nodes. The binding may also target a single cluster on the target endpoint(s).

When a client cluster requires a target for an interaction, the Binding cluster SHALL exist on the same endpoint.

Once a binding entry is created on the Binding cluster, the client endpoint MAY initiate interactions to the binding target.

### 9.6.1. Binding Mutation

If, during the creation of multiple bindings, there are no available resources to create an entry, or to establish a binding relationship, the client SHALL respond with a status of RESOURCE\_EXHAUSTED, and the binding SHALL NOT be created.

The number of bindings supported is left to the implementation. However, a device type definition MAY prescribe the minimum number of bindings supported on an endpoint. In this case, the number prescribed by the device type SHALL be supported for each fabric the node supports, unless the device type specifies otherwise. The total number of bindings supported SHALL be the sum of the requirements for each endpoint, unless the device types involved specify otherwise.

- For example, if a node supports 6 fabrics and a device type specifies at least 3 bindings must be supported, the node would need to support at least 18 bindings and ensure that at least 3 were available to every fabric.

A binding SHALL only be created with the Cluster field if the indicated client cluster exists on the endpoint.

When a binding is removed, the client endpoint SHALL end the binding relationship with the removed binding target.

### 9.6.2. Revision History

The global ClusterRevision attribute value SHALL be the highest revision number in the table below.

| Revision | Description      |
|----------|------------------|
| 1        | Initial revision |

### 9.6.3. Classification

| Hierarchy | Role    | Scope    | PICS Code |
|-----------|---------|----------|-----------|
| Base      | Utility | Endpoint | BIND      |

### 9.6.4. Cluster ID

| ID     | Name    |
|--------|---------|
| 0x001E | Binding |