

Revision	Description
1	Initial revision

9.9.2. Classification

Hierarchy	Role	Scope	PICS Code
Label	Utility	Endpoint	ULABEL

9.9.3. Cluster ID

ID	Name
0x0041	User Label

9.9.4. Attributes

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0x0000	LabelList	list[Label-Struct]	desc	N	empty	RW VM	M

9.9.4.1. LabelList Attribute

The server SHALL support the storage of up to 4 list entries in this attribute. The server MAY support the storage of more than 4 entries in this attribute.

When reading from this attribute, the server SHALL respond with the actual contents of the attribute which MAY contain any number of entries (possibly more than 4),

When writing to this attribute, a client MAY include any number of entries to be written, or none at all.

If an attempt is made to write to this attribute with a list length that is not supported by the server, the server SHALL respond with RESOURCE_EXHAUSTED.

9.10. Access Control Cluster

The Access Control Cluster exposes a data model view of a Node's Access Control List (ACL), which codifies the rules used to manage and enforce Access Control for the Node's endpoints and their associated cluster instances. Access to this Access Control Cluster itself requires a special Administrator privilege level, such that only Nodes granted such privilege (hereafter termed "Administrators") can manage the Access Control Cluster.

The Access Control Cluster SHALL be present on the [root node endpoint](#) of each Node, and SHALL NOT be present on any other Endpoint of any Node.