

Node ID 0x0000_0000_4444_4444 or 0x0000_0000_5555_5555.

E.g. an ACL entry with CASE AuthMode that grants privileges to Subject IDs [0x0000_0000_6666_6666, 0xFFFF_FFFD_ABCD_0002] (which are a Node ID and a CASE Authenticated Tag) will grant access to the Node with Node ID 0x0000_0000_6666_6666 and any Nodes with CAT identifier value 0xABCD if the CAT’s version is 0x0002 or higher. It will not grant access to Nodes with other CAT values such as 0x9999_9999. Any node with CAT identifier value of 0xABCD but version less than 0x0002 (for example: 0xFFFF_FFFD_ABCD_0001) will not be granted access.

For Group authentication, the Group ID identifies the required group, as defined in the Group Key Management Cluster.

E.g. an entry with Group AuthMode that grants privileges to Subject IDs [0x0000_0000_0000_1111, 0x0000_0000_0000_2222] (which are Group IDs) will grant access to Nodes in Group 0x1111 or 0x2222, but will not grant access to Nodes in Group 0x3333, even if they share Operational Group Keys.

Targets Field

The targets field SHALL specify a list of [AccessControlTargetStruct](#), which define the clusters on this Node to which this Access Control Entry grants access.

Device types MAY impose additional constraints on the minimum number of targets per Access Control Entry.

An attempt to create an entry with more targets than the node can support SHALL result in a RESOURCE_EXHAUSTED error and the entry SHALL NOT be created.

A single target SHALL contain at least one field (Cluster, Endpoint, or DeviceType), and SHALL NOT contain both an Endpoint field and a DeviceType field.

A target grants access based on the presence of fields as follows:

Target Semantics

Cluster	Endpoint	DeviceType	Target
			Invalid
		D	All clusters on any end-point with Descriptor containing device type D
	E		All clusters on only endpoint E
	E	D	Invalid