

Access Control Entries.

The contents SHALL consist of a [top-level anonymous list](#); each list element SHALL include a [profile-specific](#) tag encoded in [fully-qualified](#) form.

Administrators MAY iterate over this list of elements, and interpret selected elements at their discretion. The content of each element is not specified, but MAY be coordinated among manufacturers at their discretion.

E.g. a manufacturer could use this field to store structured data, including various metadata and cryptographic signatures. The manufacturer could then verify a fabric’s Access Control List by generating a canonical bytestream from the Access Control Entries for the fabric, then verifying the signature against it. Such a canonical bytestream could be generated by encoding specific entry fields and sub-fields (such as lists) in specific order and specific format (e.g. TLV).

9.10.5.8. AccessRestrictionStruct Type

This structure describes an access restriction that would be applied to a specific data model element on a given endpoint/cluster pair (see [AccessRestrictionEntryStruct](#)).

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	Type	AccessRestrictionTypeEnum	all				M
1	ID	uint32	all	X			M

Type Field

This field SHALL indicate the type of restriction, for example, AttributeAccessForbidden.

ID Field

This field SHALL indicate the element [Manufacturer Extensible Identifier \(MEI\)](#) associated with the element type subject to the access restriction, based upon the [AccessRestrictionTypeEnum](#). When the Type is AttributeAccessForbidden or AttributeWriteForbidden, this value SHALL be considered of type attrib-id (i.e. an attribute identifier). When the Type is CommandForbidden, this value SHALL be considered of type command-id (i.e. an attribute identifier). When the Type is EventForbidden, this value SHALL be considered of type event-id (i.e. an event identifier).

A null value SHALL indicate the wildcard value for the given value of Type (i.e. all elements associated with the Type under the associated endpoint and cluster for the containing AccessRestrictionEntryStruct).

9.10.5.9. AccessRestrictionEntryStruct Type

This structure describes a current access restriction on the fabric.