

```

Endpoint: 1,           // application endpoint 1
Cluster: 0x0453,       // application cluster 0x0453
Restrictions: [
  0: {
    Type: AttributeWriteForbidden, // write limitation for attribute
    Id: 0x0000                     // attribute 0x0000
  },
  1: {
    Type: CommandForbidden, // command limitation
    Id: NULL                 // all commands
  },
  2: {
    Type: EventForbidden, // event limitation
    Id: NULL              // all events
  }
]
}
]
ARL: [
  0: {
    FabricIndex: 1,           // ARL is fabric-scoped
    Endpoint: 1,             // application endpoint 1
    Cluster: 0x0453,         // application cluster 0x0453
    Restrictions: [
      0: {
        Type: AttributeWriteForbidden, // write limitation for attribute
        Id: 0x0000                     // attribute 0x0000
      }
    ]
  }
]
}

```

9.10.6.2. Administration Guidelines

The Access Control Cluster is passive in nature and is only responsible for maintaining entries in the Access Control List. It is the responsibility of Administrators to create and maintain Access Control policy by managing the list and its entries. The Access Control Cluster SHALL NOT change or remove Access Control Entries of its own volition. A device that needs to impose access restrictions upon a fabric MAY do so by adding Access Restriction Entries to the CommissioningARL and ARL attributes.

Administrators SHOULD strive to minimize resource usage by combining entries where appropriate. For example, if an Administrator is responsible for an entry that grants privilege to subject Node A, and wishes to grant the same privilege to Node B under the same conditions, then that