

Administrator SHOULD update the existing entry to apply to subject Node B as well as Node A, instead of creating a new entry. If a set of Nodes is commonly used in entries, then an Administrator MAY consider using [CASE Authenticated Tags](#) (CATs) for those entries, especially if membership in the set of Nodes changes over time.

Administrators SHOULD carefully consider the effect of Access Control Entries they manage, particularly when targeting entire Endpoints (either directly, or indirectly by Device Type), to ensure that granted privileges are appropriate for the set of Clusters that may entail. Administrators SHOULD be mindful that targeting by Device Type grants privileges to all Clusters on all Endpoints with Descriptor containing that Device Type (thereby including Clusters not part of that specified Device Type), now and in the future. Administrators SHOULD consider whether targeting specific Endpoints, or Clusters, or both, might be a more appropriate policy for the given Subjects; studying the Descriptor Cluster for affected Endpoints may help in this determination.

Administrators SHOULD be careful to avoid inadvertently removing their own administrative access. For example, an Administrator SHOULD change its own administrative access entry by updating the existing entry or by creating a new entry before removing the old entry, and SHOULD NOT remove the old entry before creating any new entry.

#### 9.10.6.3. ACL Attribute

An attempt to add an Access Control Entry when no more entries are available SHALL result in a RESOURCE\_EXHAUSTED error being reported and the ACL attribute SHALL NOT have the entry added to it. See [access control limits](#).

See the [AccessControlEntriesPerFabric](#) attribute for the actual value of the number of entries per fabric supported by the server.

Each Access Control Entry codifies a single grant of privilege on this Node, and is used by the [Access Control Privilege Granting algorithm](#) to determine if a subject has privilege to interact with targets on the Node.

#### 9.10.6.4. Extension Attribute

If present, the Access Control Extensions MAY be used by Administrators to store arbitrary [data](#) related to fabric's Access Control Entries.

The Access Control Extension list SHALL support a single extension entry per supported fabric.

#### 9.10.6.5. SubjectsPerAccessControlEntry Attribute

This attribute SHALL provide the minimum number of [Subjects](#) per entry that are supported by this server.

Since reducing this value over time may invalidate ACL entries already written, this value SHALL NOT decrease across time as software updates occur that could impact this value. If this is a concern for a given implementation, it is recommended to only use the minimum value required and avoid reporting a higher value than the required minimum.