

Instruction Field

This field SHALL provide human readable text that MAY be displayed to the user to help them locate the user interface for managing access restrictions for each fabric.

A device SHOULD implement the [Localization Configuration Cluster](#) when it has no other means to determine the locale to use for this text.

Examples include "Please try again and immediately access device display for further instructions." or "Please check email associated with your Acme account."

ARLRequestFlowUrl Field

This field SHALL indicate the URL for the service associated with the device maker which the user can visit to manage fabric limitations. The syntax of this field SHALL follow the syntax as specified in [RFC 1738](#) and SHALL use the [https](#) scheme for internet-hosted URLs.

- The URL MAY embed the token, fabric index, fabric vendor, or other information transparently in order to pass context about the originating [ReviewFabricRestrictions](#) command to the service associated with the URL. The service associated with the device vendor MAY perform vendor ID verification on the fabric from which the [ReviewFabricRestrictions](#) command originated.
- If the device grants the request, the ARL attribute in the [Access Control Cluster](#) SHALL be updated to reflect the new access rights and a successful response SHALL be returned to the device making the request using the [MTaer](#) field of the [callbackUrl](#). If the request is denied, the ARL attribute SHALL remain unchanged and a failure response SHALL be returned to the device making the request using the [MTaer](#) field of the [callbackUrl](#).
- The device using this mechanism SHALL provide a service at the URL that can accept requests for additional access and return responses indicating whether the requests were granted or denied.
- This URL will typically lead to a server which (e.g. by looking at the User-Agent) redirects the user to allow viewing, downloading, installing or using a manufacturer-provided means for guiding the user through the process to review and approve or deny the request. The device manufacturer MAY choose to use a constructed URL which is valid in a HTTP GET request (i.e. dedicated for the product) such as, for example, <https://domain.example/arl-app?vid=FFF1&pid=1234>. If a client follows or launches the ARLRequestFlowUrl, it SHALL expand it as described in [Section 9.10.9.3.4, "ARLRequestFlowUrl format"](#).
- A manufacturer contemplating using this flow should realize that
 - This flow typically requires internet access to access the URL, and access extension may fail when internet connectivity is not available.
 - If the flow prefers to redirect the user to an app which is available on popular platforms, it SHOULD also provide a fallback option such as a web browser interface to ensure users can complete access extension.

ARLRequestFlowUrl format

The [ARLRequestFlowUrl](#) SHALL contain a query component (see [RFC 3986](#) section 3.4) composed of one or more key-value pairs: