

- The query SHALL use the **&** delimiter between key/value pairs.
- The key-value pairs SHALL in the format **name=<value>** where **name** is the key name, and **<value>** is the contents of the value encoded with proper URL-encoded escaping.
- If key **MTcu** is present, it SHALL have a value of **"_"** (i.e. **MTcu=_**). This is the "callback URL (**CallbackUrl**) placeholder".
- Any key whose name begins with **MT** not mentioned in the previous bullets SHALL be reserved for future use by this specification. Manufacturers SHALL NOT include query keys starting with **MT** in the **ARLRequestFlowUrl** unless they are referenced by a version of this specification.

Any other element in the **ARLRequestFlowUrl** query field not covered by the above rules, as well as the fragment field (if present), SHALL remain including the order of query key/value pairs present.

Expansion of **ARLRequestFlowUrl** by client

Once the URL is obtained, it SHALL be expanded to form a final URL (**ExpandedARLRequestFlowUrl**) by proceeding with the following substitution algorithm on the original **ARLRequestFlowUrl**:

1. If key **MTcu** is present, compute the **CallbackUrl** desired (see [Section 9.10.9.3.5, "CallbackUrl format for ARL Request Flow response"](#)), and substitute the placeholder value **"_"** (i.e. in **MTcu=_**) in the **ARLRequestFlowUrl** with the desired contents, encoded with proper URL-encoded escaping (see [RFC 3986](#) section 2).

The final URL after expansion (**ExpandedARLRequestFlowUrl**) SHALL be the one to follow, rather than the original value obtained from the **FabricRestrictionReviewUpdate** event.

CallbackUrl format for ARL Request Flow response

If a **CallbackUrl** field (i.e. **MTcu=**) query field placeholder is present in the **ARLRequestFlowUrl**, the client MAY replace the placeholder value **"_"** in the **ExpandedARLRequestFlowUrl** with a URL that the manufacturer flow can use to make a smooth return to the client when the ARL flow has terminated.

This URL field MAY contain a query component (see [RFC 3986](#) section 3.4).

If a query is present, it SHALL be composed of one or more key-value pairs:

- The query SHALL use the **&** delimiter between key/value pairs.
- The key-value pairs SHALL follow the format **name=<value>** where **name** is the key name, and **<value>** is the contents of the value encoded with proper URL-encoded escaping.
- If key **MTaer** is present, it SHALL have a value of **"_"** (i.e. **MTaer=_**). This is the placeholder for a "access extension response" provided by the manufacturer flow to the client. The manufacturer flow SHALL replace this placeholder with the final status of the access extension request, which SHALL be formatted following [Expansion of CallbackUrl by the manufacturer custom flow](#) and encoded with proper URL-encoded escaping.
- Any key whose name begins with **MT** not mentioned in the previous bullets SHALL be reserved for future use by this specification.

Any other element in the **CallbackUrl** query field not covered by the above rules, as well as the frag-