

9.12.3. Discovery of Bridged Devices

A Node which discovers another Node with device type **Aggregator** on one of its endpoints SHOULD walk the entire tree of endpoints via the PartsList attributes and endpoints to discover the list of Bridged Devices, including their device types and other attributes, as well as any native Matter functionality potentially present on the Node.

Each endpoint found containing a **Bridged Node** device type represents a Bridged Device of the device type(s) specified at this endpoint, or one of the endpoints found via its PartsList. If the discovering Node supports this device type, it MAY add this Bridged Device to the list of devices which it could interact with, or could set up configuration for.

This discovering Node SHALL use the acquired information on the available Bridged Devices to set up (configure) (likely with input from the user) how the Bridged Devices can be used with the Matter Nodes (e.g. which switch controls which light, or how to control a light from an app on the user's phone).

Since the Bridge may expose a large number of Bridged Devices, the discovering Node SHALL use the **NodeLabel** attribute in the **Bridged Device Basic Information** cluster of each of the Bridged Devices to allow the user to easily identify and recognize the various Bridged Devices, and expedite the setup/configuration process, rather than present the user with an unannotated list of, for example, 20 lights, 3 sensors and 4 switches. These labels have likely been populated by the user when interacting previously with the Bridge e.g. through means provided by the Bridge Manufacturer, such as a Bridge Manufacturer app.

If power source-related information regarding the Bridged Device is provided in the **Power Source** cluster on the associated endpoint, the discovering Node SHOULD use this information in a similar manner as power source-related information acquired from a Matter Node's **Power Source** cluster. Such information can then be used to inform the user about the state of the power source (e.g. warn about low batteries) in a Bridged Device in a similar manner as done for Matter Nodes.

9.12.4. Configuration of Bridged Devices

For configuration of the discovered Bridged Devices, two basic archetypes are described in the following sections: one for actuators and one for sensors/switches.

Since a Bridged Device of a certain device type has the same set of application clusters as a native Matter device of the same device type, this process is similar to configuring a native Matter device of that device type.

9.12.4.1. Sending commands from a Matter controller to a Bridged Device

For Bridged Devices that are actuators and hence have a Controlee role, a Controller Node on the Fabric MAY send commands to the associated clusters on one or more endpoints on the Bridge's Node, such as an **On** command to the **On/Off** cluster of a Bridged Device. The Bridge SHALL forward this command to the relevant Bridged Device after conversion between the Matter protocol and the non-Matter device's native protocol.

Example:

A Controller creates a Group containing some Matter lights as well as some non-Matter lights, by sending an **AddGroup** command to the instances of the **Group** cluster on both the endpoints of the Matter lights as well as on the Bridge's Node endpoints representing the targeted bridged lights.