

9.14. Actions Cluster

This cluster provides a standardized way for a Node (typically a Bridge, but could be any Node) to expose logical grouping and actions.

Specifically this cluster provides:

- Information about logical grouping of endpoints on the Node (example: lights in a room)
- Information about named actions that can be performed on such a group of endpoints (example: recall a scene for a group of lights by its name)
- Commands to trigger such actions
- Events to receive feedback on the state of such actions.

The information on grouping and available actions is typically provided by the user or Bridge manufacturer via some means not defined in Matter, and therefore provided as read-only to Nodes. For example: a manufacturer-provided app allows a user to set up logical grouping and create/assign scene for such groups.

Using this cluster, a Node can learn about such logical grouping, provided actions, and trigger such actions.

While the origin of this cluster stems from use cases with a Bridge, its server side may also be implemented on any Node which can expose certain grouping, actions or automations to other users.

After defining the attributes, commands and events for this cluster, and the associated data types, several [examples](#) are provided to illustrate the capabilities of this cluster.

Actions can be defined in a flexible manner to suit the needs of the various nodes implementing this cluster. For each action, the commands available for that particular action are defined.

This cluster can be used to expose only the grouping of endpoints without any actions defined by populating the EndpointList attribute accordingly and providing an empty list for ActionList.

The term 'action' in the description of this cluster should not be confused with the term '[action](#)' as used in the Interaction Model.

9.14.1. Revision History

The global ClusterRevision attribute value SHALL be the highest revision number in the table below.

Revision	Description
1	Initial revision

9.14.2. Classification