

9.14.4.2. ActionTypeEnum Type

This data type is derived from [enum8](#).

Value	Name	Summary	Conformance
0	Other	Use this only when none of the other values applies	M
1	Scene	Bring the endpoints into a certain state	M
2	Sequence	A sequence of states with a certain time pattern	M
3	Automation	Control an automation (e.g. motion sensor controlling lights)	M
4	Exception	Sequence that will run when something doesn't happen	M
5	Notification	Use the endpoints to send a message to user	M
6	Alarm	Higher priority notification	M

Scene Value

Can be used to set a static state of the associated endpoints (typically using `InstantAction` or `InstantActionWithTransition`), or to bring these endpoints into a more dynamic state (typically using `StartAction`), where the endpoints would e.g. gradually cycle through certain colors for a pleasing effect. A voice controller could use "set" (to map to `InstantAction`) or "play" (to map to `StartAction`) to trigger such actions.

Example: see [Section 9.14.8.1, "Example 1: Scene recall"](#) and [Section 9.14.8.2, "Example 2: Set dynamic light effect"](#).

Sequence Value

Indicates an action which involves a sequence of events/states of the associated endpoints, such as a wake-up experience.

Example: see [Section 9.14.8.4, "Example 4: Wake-up routine"](#).

Automation Value

Indications an automation (e.g. a motion sensor controlling lights, an alarm system) which can be e.g. started, stopped, paused, resumed.

Example: see [Section 9.14.8.3, "Example 3: Pause sensor automation"](#).