

9.14.6.12. DisableActionWithDuration Command

This command is used to disable an action with a duration.

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	ActionID	uint16	all			M
1	InvokeID	uint32	all			O
2	Duration	uint32	all		MS	M

This command disables a certain action or automation, and SHALL change the action's state to Disabled. After the specified Duration, the action or automation will re-start, and the action's state SHALL change to either Inactive or Active, depending on the actions (see [Section 9.14.8.4, "Example 4: Wake-up routine"](#) and [Section 9.14.8.6, "Example 6: Alarm system"](#)).

Example: disable a "wakeup" experience for a period of 1 week when going on holiday (to prevent them from turning on in the morning while you're not at home). After this period, the wakeup experience will control the lights as before.

Duration Field

This field SHALL indicate the requested duration in seconds.

9.14.7. Events

ID	Name	Priority	Access	Conformance
0x00	StateChanged	INFO	V	M
0x01	ActionFailed	INFO	V	M

9.14.7.1. StateChanged Event

This event SHALL be generated when there is a change in the State of an ActionID during the execution of an action *and* the most recent command using that ActionID used an InvokeID data field.

It provides feedback to the client about the progress of the action.

Example: When InstantActionWithTransition is invoked (with an InvokeID data field), two StateChanged events will be generated:

- one when the transition starts (NewState=Active)
- one when the transition completed (NewState=Inactive)

This event SHALL have the following data fields:

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	ActionID	uint16				M