

ID	Name	Type	Constraint	Quality	Fallback	Conformance
1	InvokeID	uint32				M
2	NewState	ActionStateEnum				M

ActionID Field

This field SHALL be set to the ActionID of the action which has changed state.

InvokeID Field

This field SHALL be set to the InvokeID which was provided to the most recent command referencing this ActionID.

NewState Field

This field SHALL be set to state that the action has changed to.

9.14.7.2. ActionFailed Event

This event SHALL be generated when there is some error which prevents the action from its normal planned execution *and* the most recent command using that ActionID used an InvokeID data field.

It provides feedback to the client about the non-successful progress of the action.

Example: When InstantActionWithTransition is invoked (with an InvokeID data field), and another controller changes the state of one or more of the involved endpoints during the transition, thus interrupting the transition triggered by the action, two events would be generated:

- StateChanged when the transition starts (NewState=Active)
- ActionFailed when the interrupting command occurs (NewState=Inactive, Error=interrupted)

Example: When InstantActionWithTransition is invoked (with an InvokeID data field = 1), and the same client invokes an InstantAction with (the same or another ActionId and) InvokeID = 2, and this second command interrupts the transition triggered by the first command, these events would be generated:

- StateChanged (InvokeID=1, NewState=Active) when the transition starts
- ActionFailed (InvokeID=2, NewState=Inactive, Error=interrupted) when the second command interrupts the transition
- StateChanged (InvokeID=2, NewState=Inactive) upon the execution of the action for the second command

This event SHALL have the following data fields: