

Bit	Code	Feature	Conformance	Summary
0	CIP	CheckInProtocol-Support	LITS, O	Device supports attributes and commands for the Check-In Protocol support.
1	UAT	UserActiveMode-Trigger	LITS, O	Device supports the user active mode trigger feature.
2	LITS	LongIdleTimeSupport	O	Device supports operating as a Long Idle Time ICD .
3	DSLS	DynamicSitLitSupport	[LITS]	Device supports dynamic switching from SIT to LIT operating modes .

9.16.4.1. CheckInProtocolSupport Feature

When this feature is supported, the device SHALL support all the associated commands and attributes to properly support the [Check-In Protocol](#).

9.16.4.2. UserActiveModeTrigger Feature

This feature is supported if and only if the device has a [user active mode trigger](#).

9.16.4.3. LongIdleTimeSupport Feature

This feature is supported if and only the device is a [Long Idle Time ICD](#).

9.16.4.4. DynamicSitLitSupport Feature

This feature is supported if and only if the device can switch between SIT and LIT operating modes even if it has a valid registered client. See the [dynamic SIT / LIT operating mode switching](#) for more details.

9.16.5. Data Types

9.16.5.1. UserActiveModeTriggerBitmap Type

This data type is derived from map32. See the [UserActiveModeTriggerHint table](#) for requirements associated to each bit.