

- If the ICD is operating as a LIT ICD, OperatingMode SHALL be LIT.
- If the ICD is operating as a SIT ICD, OperatingMode SHALL be SIT.

9.16.6.10. MaximumCheckInBackoff Attribute

This attribute SHALL indicate the maximum time in seconds between two Check-In messages when [back-off](#) is active. The MaximumCheckInBackoff SHALL NOT be smaller than the [IdleModeDuration](#).

If the MaximumCheckInBackoff is equal to the [IdleModeDuration](#), it means the ICD does not [back-off](#).

9.16.7. Commands

ID	Name	Direction	Response	Access	Conformance
0x00	RegisterClient	client ⇒ server	RegisterClientResponse	M F	CIP
0x01	RegisterClientResponse	client ⇐ server	N		CIP
0x02	UnregisterClient	client ⇒ server	Y	M F	CIP
0x03	StayActiveRequest	client ⇒ server	StayActiveResponse	O	LITS, O
0x04	StayActiveResponse	client ⇐ server	N		LITS, O

9.16.7.1. RegisterClient Command

This command allows a client to register itself with the ICD to be notified when the device is available for communication.

This command SHALL have the following data fields:

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	CheckInNodeID	node-id	all			M
1	MonitoredSubject	subject-id	all			M
2	Key	octstr	16			M
3	VerificationKey	octstr	16			O
4	ClientType	ClientTypeEnum	all			M