

- a. If the verification key does not have a valid value, the status SHALL be FAILURE. the server SHALL continue from step 6.
 - b. If the verification key is not equal to the Key value stored in the entry, the status SHALL be FAILURE. The server SHALL continue from step 6.
 - c. If the verification key is equal to the Key value stored in the entry, the server SHALL continue from step 4.
4. The entry SHALL be updated with the received CheckInNodeID, MonitoredSubject, Key and ClientType.
 - a. If the update fails, the status SHALL be FAILURE. The server SHALL continue from step 6.
 - b. If the update succeeds, the server SHALL continue from step 5.
5. The server SHALL persist the client information.
 - a. If the persistence fails, the status SHALL be FAILURE and the server SHALL continue from step 6.
 - b. If the persistence succeeds, the status SHALL be SUCCESS and the server SHALL continue from step 6.
6. The server SHALL generate a response.
 - a. If the status is SUCCESS, the server SHALL generate a RegisterClientResponse command.
 - b. If the status is not SUCCESS, the server SHALL generate a default response with the Status field set to the evaluated error status.

9.16.7.2. RegisterClientResponse Command

This command SHALL be sent by the ICD Management Cluster server in response to a successful RegisterClient command.

This command SHALL have the following data fields:

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	ICDCounter	uint32	all			M

When Generated

This command SHALL be generated in response to a successful RegisterClient command. The ICD-Counter field SHALL be set to the ICDCounter attribute of the server.

9.16.7.3. UnregisterClient Command

This command allows a client to unregister itself with the ICD. Example: a client that is leaving the network (e.g. running on a phone which is leaving the home) can (and should) remove its subscriptions and send this UnregisterClient command before leaving to prevent the burden on the ICD of an absent client.

This command SHALL have the following data fields: