

4. The server SHALL verify that the received verification key is equal to the key previously stored in the list of registered clients with the matching CheckInNodeID.

a. If the verification key does not have a valid value, the status SHALL be FAILURE. the server SHALL continue from step 6.

b. If the verification key is not equal to the Key value stored in the entry, the status SHALL be FAILURE. The server SHALL continue from step 6.

c. If the verification key is equal to the Key value stored in the entry, the server SHALL continue from step 5.
5. The server SHALL delete the entry with the matching CheckInNodeID from storage and will persist the change.

a. If the removal of the entry fails, the status SHALL be FAILURE. The server SHALL continue from step 6.

b. If the removal succeeds, the status SHALL be SUCCESS and the server SHALL continue to step 6.
6. The server SHALL generate a response with the Status field set to the evaluated status.

9.16.7.4. StayActiveRequest Command

This command allows a client to request that the server stays in active mode for at least a given time duration (in milliseconds) from when this command is received.

This command SHALL have the following data fields:

ID	Name	Type	Constraint	Quality	Fallback	Conformance
0	StayActive-Duration	uint32	all			M

This StayActiveDuration MAY be longer than the ActiveModeThreshold value and would, typically, be used by the client to request the server to stay active and responsive for this period to allow a sequence of message exchanges during that period. The client MAY slightly overestimate the duration it wants the ICD to be active for, in order to account for network delays.

Effect on Receipt

When receiving a StayActiveRequest command, the server SHALL calculate the maximum PromisedActiveDuration it can remain active as the greater of the following two values:

- StayActiveDuration: Specified in the received command by the client.

• Remaining Active Time: The server’s planned remaining active time based on the ActiveMode-Threshold and its internal resources and power budget.

A server MAY replace StayActiveDuration with Minimum Active Duration in the above calculation.

PromisedActiveDuration represents the guaranteed minimum time the server will remain active, taking into account both the requested duration and the server’s capabilities.