

and where a context-specific tag is used, any context-specific tag not listed in a given schema SHALL be reserved for future use and SHALL be silently ignored by clients and servers if seen in a payload.

10.2.2.1. Message Header Encoded Action Information

The following Common Action Information fields are encoded into the message header:

Header Field	Type	Description
Message Exchange ID	16-bit integer	Used to convey the Transaction ID
Source Node ID	64-bit integer	Node ID of the source that generated the transaction
Destination ID	64-bit integer	Either a Node ID or Group ID is encoded in here depending on what the IM indicates
Protocol ID	32 bits	The protocol to which this message belongs; all messages in this spec SHALL use the PROTOCOL_ID_INTERACTION_MODEL Protocol ID
Protocol OpCode	8 bits	The specific message type

10.2.2.2. Context Tag Encoded Action Information

The following Common Action Information fields are encoded as context tagged fields in the action message payload. All action messages defined in [Section 10.7, “Message Definitions”](#) SHALL include these tagged fields:

Common Action Field	Context Tag
InteractionModelRevision	0xFF

10.2.3. Chunking

Chunking is the act of splitting an Action that contains attribute/event data, specifically ReportData and WriteRequest actions, into multiple messages at logical boundaries due to the size limitations imposed by IPv6 for UDP packets (see [Section 4.4.4, “Message Size Requirements”](#) for more details).

Since attribute/event data within Actions are already organized into a series of [AttributeDataIBs](#) (for attributes) and [EventDataIBs](#) for event records, chunking entails maximally packing these information blocks (IBs) into a series of 'data' messages.

To ensure in-order delivery of a chunked set of IBs, each data message requires a response before the next data message can be sent. For [ReportDataMessage](#) and [WriteRequestMessage](#), a [StatusResponseMessage](#) and [WriteResponseMessage](#) are the respective response messages.

A [MoreChunkedMessages](#) flag SHALL be set on every data message except the last to convey to the