

| ID | Name          | Type       | Constraint | Quality | Fallback  | Conformance |
|----|---------------|------------|------------|---------|-----------|-------------|
| 0  | <b>Speed</b>  | uint8      | max 200    |         | MS*       | M           |
| 1  | <b>Rotate</b> | RotateEnum | all        |         | Clockwise | O           |

**\*Spec Writer Note**

*"MS" means Manufacturer Specific.*

**Speed Field**

This field SHALL indicate the rotation speed.

**Rotate Field**

This field SHALL indicate the rotation direction.

**10.4.1.8.2. StopRequest Command**

Upon receipt, this SHALL stop the disco ball rotating, and SHALL set the Run, Speed and Rotate attributes to 0.

**10.4.1.8.3. ReverseRequest Command**

Upon receipt, this SHALL reverse the direction of the disco ball rotation. This command MAY generate an error response of UNSUPPORTED\_PATTERN.

**10.4.1.8.4. WobbleRequest Command**

Upon receipt, this SHALL wobble the disco ball on its axis at the speed in the WobbleSpeed attribute. This command MAY generate an error response of UNSUPPORTED\_PATTERN.

**10.4.1.8.5. PatternRequest Command**

| ID | Name            | Type   | Constraint | Quality | Fallback | Conformance |
|----|-----------------|--------|------------|---------|----------|-------------|
| 0  | <b>Passcode</b> | string | max 6      |         | empty    | M           |

**Passcode Field**

If the passcode field is an empty string, this SHALL start the disco ball rotating using unprotected (i.e patterns that have no passcode) pattern list entries in sequence to control the disco ball. When the final entry in the list is processed the sequence SHALL restart at the first entry.

If the passcode field is not an empty string, only the patterns that correspond to the provided passcode SHALL be invoked.