

Attribute are re-used from Path1
Path4 = [[Node = 0x18B430003020203, Endpoint = 20, Cluster = Disco Ball, Attribute = Axis]] // Reset tracker variables
Path5 = [[EnableTagCompression = true, Attribute = Pattern, ListIndex = 5]] // Node, Endpoint, Cluster are re-used from Path4.

10.6.3. DataVersionFilterIB

TLV Type: Structure					
Element	Comments	Tag Type	Tag Number	Type	Range
Path		Context Tag	0	ClusterPathIB	-
DataVersion		Context Tag	1	Unsigned Int	32 bits

10.6.4. AttributeDataIB

TLV Type: Structure					
Element	Comments	Tag Type	Tag Number	Type	Range
DataVersion		Context Tag	0	Unsigned Int	32 bits
Path		Context Tag	1	AttributePathIB	-
Data		Context Tag	2	Variable (see below)	-

- The **Change** field in the Interaction Model specification is not encoded directly. Instead, it is encoded through the use of special values in the **Path** and **Data** fields (see [Section 10.6.4.3.1, “Lists”](#)).

10.6.4.1. DataVersion

This tag can be omitted if the value of **EnableTagCompression** in the Path field is true. In this case, the value for the omitted tag SHALL be set to the value for that tag (if present) in the last AttributeDataIB that had tag compression disabled (i.e **EnableTagCompression** not present or set to false) and was seen in a message that is part of the same interaction model Action as the current message. If this tag was not present and tag compression was disabled, it SHALL be interpreted as though a data version was not specified in that, or subsequent AttributeDataIBs.

NOTE

Support for encoding using the EnableTagCompression tag is provisional.

10.6.4.2. Path

In addition to the rules specified for [AttributePathIB](#), the **Attribute** and 'Cluster' fields within that element SHALL always be present.