

This option SHOULD be selected when sending AttributeReports as a part of a ReportDataMessage, when it is NOT possible to encode the entirety of the list in a single [AttributeDataIB](#) that fits in a single message.

This option SHOULD also be selected when modifying the ACL or Extension attribute of the [Access Control Cluster](#) as part of a WriteRequestMessage, when it is NOT possible to encode the entirety of the list in a single [AttributeDataIB](#) that fits in a single message.

This option SHALL NOT be used in a WriteRequestMessage for other list attributes.

Because lists may be processed in chunks or by item, clients that receive an error status for a write action to a list attribute SHOULD NOT assume that the list contents are unchanged.

10.6.4.4. Examples

10.6.4.4.1. Simple Types

Update a top-level attribute:

```
AttributeDataIB = {  
    DataVersion = 1,  
    Path = [[ Endpoint = 10, Cluster = Disco Ball, FieldID = Axis ]],  
    Data = 90  
}
```

10.6.4.5. Collection Types (List)

Add an item to a list:

```
AttributeDataIB = {  
    DataVersion = 1,  
    Path = [[ Endpoint = 10, Cluster = Disco Ball, FieldID = Pattern, ListIndex =  
null]],  
    Data = {  
        Duration = 100,  
        Rotate = Counterclockwise, // On the wire enum value (2) is used  
        Speed = 12,  
        Axis = 90,  
        // WobbleSpeed omitted; this cluster instance does not support Wobble  
        Passcode = "9876"  
    }  
}
```

Replace a list (Single IB):