

```

    Axis = 90,
    // WobbleSpeed omitted; this cluster instance does not support Wobble
    Passcode = "9876"
  }
}

```

Modifying or deleting single list items SHALL be done by completely replacing the list with the options provided above.

10.6.5. AttributeReportIB

TLV Type: Structure (Anonymous)					
Element	Comments	Tag Type	Tag Number	TLV Type	Range
AttributeSta-tus		Context Tag	0	AttributeSta-tusIB	-
AttributeData		Context Tag	1	Attribute-DataIB	-

10.6.6. EventFilterIB

TLV Type: Structure (Anonymous)					
Element	Comments	Tag Type	Tag Number	TLV Type	Range
Node		Context Tag	0	Unsigned Int	64 bits
EventMin		Context Tag	1	Unsigned Int	64 bits

- The **Node** tag MAY be omitted if the target node of the path matches the NodeID of the server involved in the interaction.

10.6.7. ClusterPathIB

TLV Type: List					
Element	Comments	Tag Type	Tag Number	TLV Type	Range
Node		Context Tag	0	Unsigned Int	64 bits
Endpoint		Context Tag	1	Unsigned Int	16 bits
Cluster		Context Tag	2	Unsigned Int	32 bits

- The **Node** tag MAY be omitted if the target node of the path matches the NodeID of the server involved in the interaction.
- If the **Group** field is present, the Group ID is encoded in the **DST** field in the message header and elided from the encoding here.