

10.6.12. CommandDataIB

TLV Type: Structure (Anonymous)					
Element	Comments	Tag Type	Tag Number	Type	Range
CommandPath		Context Tag	0	Command-PathIB	-
CommandFields	Optional	Context Tag	1	variable	-
CommandRef	Optional	Context Tag	2	Unsigned Int	16 bits

10.6.12.1. CommandFields

This field SHALL contain the full set of arguments as specified in the description of the command request/response. The arguments SHALL follow the rules of encoding as provided in [Data Types](#).

The entirety of the arguments SHALL be encapsulated in a TLV structure, with each argument encoded appropriately using its field id as the context tag number.

If there are no arguments in the Request or Response, this tag MAY be omitted entirely.

10.6.12.2. CommandRef

This field SHALL contain an unsigned integer used to correlate responses to commands with the requests that led to those responses.

10.6.12.3. Examples

Request + Response:

```
RequestCommandElement = {
    CommandPath = [[ Endpoint = 10, Cluster = Disco Ball, Command = Stats Request ]],
    CommandFields = {} // Empty CommandFields MAY be encoded as an empty container
    CommandRef = 17
}

ResponseCommandElement = {
    CommandPath = [[ Endpoint = 10, Cluster = Disco Ball, Command = Stats Response ]],
    CommandFields = {
        LastRun = 100,
        Patterns = 1
    }
    CommandRef = 17 // the same number as in the request
}
```

Empty request: