

```

RequestCommandElement = {
    CommandPath = [[ Endpoint = 10, Cluster = Disco Ball, Command = Stop Request ]]
    // Empty CommandFields MAY also be omitted entirely
    // CommandRef MAY be omitted when the request contains only a single CommandDataIB
}

// No cluster specific response is returned; a status is passed via Invoke Response at
the Interaction layer

```

10.6.13. InvokeResponseIB

TLV Type: Structure (Anonymous)					
Element	Comments	Tag Type	Tag Number	Type	Range
Command		Context Tag	0	Command-DataIB	-
Status		Context Tag	1	CommandStatusIB	-

10.6.14. CommandStatusIB

TLV Type: Structure					
Element	Comments	Tag Type	Tag Number	Type	Range
CommandPath		Context Tag	0	Command-PathIB	-
Status		Context Tag	1	StatusIB	-
CommandRef	Optional	Context Tag	2	Unsigned Int	16 bits

10.6.14.1. CommandRef

This field SHALL contain an unsigned integer used to correlate responses to commands with the requests that led to those responses.

10.6.15. EventStatusIB

TLV Type: Structure					
Element	Comments	Tag Type	Tag Number	Type	Range
Path		Context Tag	0	EventPathIB	-
Status		Context Tag	1	StatusIB	-