

10.7.2.1. AttributeRequests

- If not present SHALL be treated as an empty list.

10.7.2.2. EventRequests

- If not present SHALL be treated as an empty list.
- Omission of any of the **Endpoint**, **Cluster**, **Event** tags indicates wildcard semantics.

10.7.2.3. EventFilters

- If not present SHALL be treated as an empty list.
- MAY be ignored (i.e. not decoded) if **EventRequests** is empty.

10.7.2.4. DataVersionFilters

- If not present SHALL be treated as an empty list.
- MAY be ignored (i.e. not decoded) if **AttributeRequests** is empty.

10.7.3. ReportDataMessage

TLV Type: Structure (Anonymous)					
Element	Comments	Tag Type	Tag Number	Type	Range
SubscriptionID	Optional	Context Tag	0	Unsigned Integer	32 bits
AttributeReports	Optional	Context Tag	1	Array of AttributeReportIB	
EventReports	Optional	Context Tag	2	Array of EventReportIB	
MoreChunkedMessages	Can be omitted if false.	Context Tag	3	Boolean	-
SuppressResponse	Omit if 'false'	Context Tag	4	Boolean	-

- Multiple ReportDataMessages SHALL be sent if a Report Data action does not fit into a single message. In this case all the ReportDataMessages except the last one SHALL have **MoreChunkedMessages** set to true.
- For each ReportDataMessage received, a successful StatusResponse message SHALL be sent back to the sender unless **SuppressResponse** is true.
- If **MoreChunkedMessages** is true, **SuppressResponse** SHALL be false.
- If **MoreChunkedMessages** is false, **SuppressResponse** SHALL be set to the SuppressResponse value in the Report Data action being encoded.